



Bearing company



6306lu Bearing 2D drawings and 3D CAD models

30,000 mm x 72,000 mm x 19,000 mm ntn
6306lu bearing

Bearing No. 6306lu

Size	30x72x19 mm
Bore Diameter	30,000 mm
Outer Diameter	72,000 mm
Width	19,000 mm
d	30,000 mm
D	72,000 mm
B	19,000 mm
C	19,000 mm
rs min	1.1 mm
Radial clearance class	CN
Mass	0.36 kg
Dynamic load, C	26.7 kN
Static load, C0	15 kN
Fatigue limit load, Cu	0.68 kN
f0	13.3
Nlim (grease)	6,600 rpm
Min operating temperature, Tmin	-25 ° C
Max operating temperature, Tmax	110 ° C
Characteristic cage frequency, FTF	0.39 Hz
Characteristic rolling element frequency, BSF	4.14 Hz
Characteristic outer ring frequency, BPF0	3.08 Hz
Characteristic inner ring	4.92 Hz



Bearing company

frequency, BPFI	
da min	36.5 mm
da max	43 mm
Da max	65.5 mm
ra max	1 mm
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.344
EAN	4547359387896
Product Group	B00308
Enclosure	1 Seal
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	30MM Bore; 72MM Outside Diameter; 19MM Outer Race Width; 1 Seal; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage; C
Other Features	Deep Groove Double Lip Friction Nitrile Rubber Seal -20 To 120 Deg C
Category	Single Row Ball Bearing



Bearing company

UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.ntnamerica.com
Manufacturer Item Number	6306LU
Weight / LBS	0.758
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	0.748 Inch 19 Millimeter
Bore	1.181 Inch 30 Millimeter
Outside Diameter	2.835 Inch 72 Millimeter
bore diameter:	30 mm
precision rating:	ISO Class 0
outside diameter:	72 mm
finish/coating:	Uncoated
overall width:	19 mm
bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Single Seal
inner ring width:	19 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	19 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	6600 rpm
internal clearance:	CN
fillet radius:	1.1 mm
operating temperature range:	-40 to 120 ° C
maximum rpm:	6600 RPM
dynamic load capacity:	26700 N
series:	63



Bearing company

static load capacity:	15000 N
manufacturer product page:	Click here