



Bearing company



20 mm x 42 mm x 12 mm koyo 6004 bearing

Bearing No. 6004

6004 Bearing 2D drawings and 3D CAD models

| | |
|-------------------------------|--------------------------|
| Size | 20x42x12 mm |
| Bore Diameter | 20 mm |
| Outer Diameter | 42 mm |
| Width | 12 mm |
| d | 20 mm |
| D | 42 mm |
| B | 12 mm |
| C | 12 mm |
| r min. | 0,6 mm |
| da min. | 24 mm |
| Da max. | 38 mm |
| ra max. | 0,6 mm |
| Weight | 0,069 Kg |
| Basic dynamic load rating (C) | 9,4 kN |
| Basic static load rating (C0) | 5,05 kN |
| (Grease) Lubrication Speed | 17000 r/min |
| (Oil) Lubrication Speed | 21000 r/min |
| Category | Single Row Ball Bearings |
| Inventory | 0.0 |
| Manufacturer Name | KOYO |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.073 |
| EAN | 0605790043437 |
| Product Group | B00308 |
| Enclosure | Open |
| Precision Class | ABEC 1 ISO P0 |



Bearing company

| | |
|---------------------------------|--|
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Internal Clearance | C0-Medium |
| Inch - Metric | Metric |
| Long Description | 20MM Bore; 42MM Outside Diameter; 12MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features |
| Category | Single Row Ball Bearing |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Manufacturer URL | http://www.koyousa.com |
| Manufacturer Item Number | 6004 |
| Weight / LBS | 0.161 |
| Outside Diameter | 1.654 Inch 42 Millimeter |
| Bore | 0.787 Inch 20 Millimeter |
| Outer Race Width | 0.472 Inch 12 Millimeter |
| Bearing No. | 6004 |
| r(min) | 0.6 |
| Cr | 11.7 |
| C0r | 5.05 |
| Cu | 0.350 |
| f0 | 13.9 |
| Grease lub. | 17000 |
| Oil lub. | 21000 |
| | |



Bearing company

| | |
|------------------|-------|
| da(min) | 24 |
| Da(max) | 38 |
| ra(max) | 0.6 |
| (Refer.)Mass(kg) | 0.069 |