



## Bearing company



### 15 mm x 28 mm x 7 mm skf 61902 bearing

Bearing No. 61902

Size	15x28x7 mm
Bore Diameter	15 mm
Outer Diameter	28 mm
Width	7 mm
d	15 mm
D	28 mm
B	7 mm
C	7 mm
d1	18,8 mm
r1 min.	0,3 mm
r2 min.	0,3 mm
D1	24,2 mm
D2	25,3 mm
da min.	17 mm
Da max.	26 mm
rc max.	0,3 mm
Weight	0,016 Kg
Basic dynamic load rating (C)	4,36 kN
Basic static load rating (C0)	2,24 kN
Fatigue load limit (Pu)	0,095
Reference speed	56000 r/min
Limiting speed	34000 r/min
Calculation factor (f0)	14
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	SKF

61902 Bearing 2D drawings and 3D CAD models



## Bearing company

Minimum Buy Quantity	N/A
Weight / Kilogram	0.01
EAN	7316577094988
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	15MM Bore; 28MM Outside Diameter; 7MM Outer Race Diameter; Open; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	61902
Weight / LBS	0.03
Bore	0.591 Inch   15 Millimeter
Outer Race Width	0.276 Inch   7 Millimeter
Outside Diameter	1.102 Inch   28 Millimeter
bore diameter:	15 mm
static load capacity:	2.24 kN



## Bearing company

outside diameter:	28 mm
precision rating:	Not Rated
overall width:	7 mm
finish/coating:	Uncoated
bore type:	Round
cage material:	Steel
closure type:	Open
outer ring width:	7 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	0.3 mm
snap ring included:	Without Snap Ring
maximum rpm:	34000 RPM
internal clearance:	C0
series:	61
dynamic load capacity:	4.36 kN
$d_1$	18.8 mm
$D_2$	0 mm
$r_{1,2}$ min.	0.3 mm
$d_a$ min.	17 mm
$D_a$ max.	26 mm
$r_a$ max.	0.3 mm
Basic dynamic load rating C	4.36 kN
Basic static load rating $C_0$	2.24 kN
Fatigue load limit $P_u$	0.095 kN
Calculation factor $k_r$	0.02
Calculation factor $f_0$	14.3
Mass bearing	0.016 kg