



Bearing company



6228 Bearing 2D drawings and 3D CAD models

140 mm x 250 mm x 42 mm skf 6228 bearing

Bearing No. 6228

| | |
|---|--------------------------|
| Size | 250x140x42 mm |
| Bore Diameter | 250 mm |
| Outer Diameter | 140 mm |
| Width | 42 mm |
| d | 140 mm |
| D | 250 mm |
| B | 42 mm |
| d ₁ | 175.5 mm |
| D ₁ | 212.5 mm |
| r _{1,2} - min. | 3 mm |
| d _a - min. | 154 mm |
| D _a - max. | 236 mm |
| r _a - max. | 2.5 mm |
| Basic dynamic load rating - C | 165 kN |
| Basic static load rating - C ₀ | 150 kN |
| Fatigue load limit - P _u | 4.6 kN |
| Reference speed | 5300 r/min |
| Limiting speed | 3400 r/min |
| Calculation factor - k _r | 0.025 |
| Calculation factor - f ₀ | 14.9 |
| Category | Single Row Ball Bearings |
| Inventory | 2.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 7.78 |



Bearing company

| | |
|---------------------------------|--|
| EAN | 7316576623141 |
| Product Group | B00308 |
| Enclosure | Open |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Internal Clearance | C0-Medium |
| Inch - Metric | Metric |
| Long Description | 140MM Bore; 250MM Outside Diameter; 42MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features |
| Category | Single Row Ball Bearing |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Manufacturer URL | http://www.skf.com |
| Manufacturer Item Number | 6228 |
| Weight / LBS | 17.14 |
| Bore | 5.512 Inch 140 Millimeter |
| Outside Diameter | 9.843 Inch 250 Millimeter |
| Outer Race Width | 1.654 Inch 42 Millimeter |
| bore diameter: | 140 mm |
| static load capacity: | 150 kN |
| outside diameter: | 250 mm |
| precision rating: | ABEC 1 (ISO Class |



Bearing company

| | |
|--------------------------------|--------------------------|
| | Normal) |
| overall width: | 42 mm |
| finish/coating: | Uncoated |
| bore type: | Round |
| cage material: | Steel |
| closure type: | Open |
| outer ring width: | 42 mm |
| row type & fill slot: | Single Row Non-Fill Slot |
| fillet radius: | 2.5 mm |
| snap ring included: | Without Snap Ring |
| maximum rpm: | 3400 RPM |
| internal clearance: | C0 |
| series: | 62 |
| dynamic load capacity: | 165 kN |
| d_1 | 175.5 mm |
| D_1 | 212.5 mm |
| $r_{1,2}$ min. | 3 mm |
| d_a min. | 154 mm |
| D_a max. | 236 mm |
| r_a max. | 2.5 mm |
| Basic dynamic load rating C | 165 kN |
| Basic static load rating C_0 | 150 kN |
| Fatigue load limit P_u | 4.55 kN |
| Calculation factor k_r | 0.025 |
| Calculation factor f_0 | 14.9 |
| Mass bearing | 7.77 kg |