




Bearing company



55 mm x 80 mm x 13 mm skf 61911 bearing

Bearing No. 61911

Size	80x55x13 mm
Bore Diameter	80 mm
Outer Diameter	55 mm
Width	13 mm
d	55 mm
D	80 mm
B	13 mm
d ₁	63.2 mm
D ₁	71.8 mm
r _{1,2} - min.	1 mm
d _a - min.	59.6 mm
D _a - max.	75.4 mm
r _a - max.	1 mm
Basic dynamic load rating - C	16.5 kN
Basic static load rating - C ₀	14 kN
Fatigue load limit - P _u	0.6 kN
Reference speed	17000 r/min
Limiting speed	11000 r/min
Calculation factor - k _r	0.02
Calculation factor - f ₀	16.3
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.202

61911 Bearing 2D drawings and 3D CAD models



Bearing company

EAN	7316577095053
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	55MM Bore; 80MM Outside Diameter; 13MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	61911
Weight / LBS	0.44
Outside Diameter	3.15 Inch 80 Millimeter
Outer Race Width	0.512 Inch 13 Millimeter
Bore	2.165 Inch 55 Millimeter
bore diameter:	55 mm
static load capacity:	14 kN
outside diameter:	80 mm
precision rating:	Not Rated



Bearing company

overall width:	13 mm
finish/coating:	Uncoated
bore type:	Round
cage material:	Steel
closure type:	Open
outer ring width:	13 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	1 mm
snap ring included:	Without Snap Ring
maximum rpm:	11000 RPM
internal clearance:	C0
series:	61
dynamic load capacity:	16.5 kN
d_1	63 mm
D_1	72.3 mm
$r_{1,2}$ min.	1 mm
d_a min.	59.6 mm
D_a max.	75.4 mm
r_a max.	1 mm
Basic dynamic load rating C	16.5 kN
Basic static load rating C_0	14 kN
Fatigue load limit P_u	0.6 kN
Calculation factor k_r	0.02
Calculation factor f_0	16.3
Mass bearing	0.19 kg