



## Bearing company



7324 bcbm Bearing 2D drawings and 3D CAD models

120 mm x 260 mm x 55 mm skf 7324 bcbm bearing

Bearing No. 7324 bcbm

Category	Angular Contact Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	13.85
EAN	7316576651052
Product Group	B00308
Enclosure	Open
Flush Ground	Yes
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 3   ISO P6
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Brass
Contact Angle	40 Degree
Internal Clearance	CB
Number of Bearings	1 (Single)
Mounting Arrangement	Universal
Inch - Metric	Metric
Long Description	120MM Bore; 260MM Outside Diameter; 55MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Balls; ABEC 3   ISO P6; No Filling Slot; No Snap



## Bearing company

	Ring
Other Features	Normal Axial Internal Clearance
Category	Angular Contact Ball Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	7324 BCBM
Weight / LBS	30.497
B	2.165 Inch   55 Millimeter
D	10.236 Inch   260 Millimeter
d	4.724 Inch   120 Millimeter
bore diameter:	120 mm
radial static load capacity:	250 kN
outside diameter:	260 mm
cage material:	Brass
overall width:	55 mm
outer ring width:	55 mm
contact angle:	40 °
maximum rpm:	3000 RPM
row type & fill slot:	Single-Row Non-Fill Slot
finish/coating:	Uncoated
internal clearance:	C0
precision rating:	ABEC 3 (ISO Class 6)
closure type:	Open
fillet radius:	2.5 mm
radial dynamic load capacity:	238 kN
series:	73
d	120 mm



## Bearing company

D	260 mm
B	55 mm
$d_1$	178.4 mm
$d_2$	153.85 mm
$D_1$	211 mm
a	107 mm
$r_{1,2}$ min.	3 mm
$r_{3,4}$ min.	1.5 mm
$d_a$ min.	134 mm
$D_a$ max.	246 mm
$D_b$ max.	253 mm
$r_a$ max.	2.5 mm
$r_b$ max.	1 mm
Basic dynamic load rating C	238 kN
Basic static load rating $C_0$	250 kN
Fatigue load limit $P_u$	7.65 kN
Reference speed	3000 r/min
Limiting speed	3600 r/min
Calculation factor A	1.11
Calculation factor $k_r$	0.09
Calculation factor e	1.14
Calculation factor X	0.35
Calculation factor $Y_0$	0.26
Calculation factor $Y_2$	0.57
Calculation factor X	0.57
Calculation factor $Y_0$	0.52
Calculation factor $Y_1$	0.55
Calculation factor $Y_2$	0.93
Mass bearing	14.5 kg